Safety Data Sheet 94052 ElectroKleneTM



Copying and/or downloading of this information for the purpose of properly utilizing Stoner Inc. product is allowed provided that: (1) the information is copied in full with no changes unless prior agreement is obtained from Stoner Inc., & (2) neither the copy nor the original is resold or otherwise distributed with intention of earning profit thereon.

1. IDENTIFICATION

Stoner Incorporated 1070 Robert Fulton Hwy. Quarryville, PA 17566 1-800-227-5538 Product Name: ElectroKleneTM
Product Code: 94052

Product Use: Electronic Cleaner

24-hour emergency phone: 1-800-424-9300 [CHEMTREC]

2. HAZARD IDENTIFICATION

POTENTIAL HEALTH EFFECTS

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Hazard Symbols





GHS Classification Gases under pressure - Liquified Gas

Aspiration Hazard Category 1

Acute Toxicity - Inhalation Gas Category 4

Simple Asphyxiant Category 1

Signal Word Danger

Hazard Statements Contains gas under pressure; may explode if heated.

May be fatal if swallowed and enters airways.

Harmful if inhaled.

May displace oxygen and cause rapid suffocation

Precautionary Statements

Prevention Avoid breathing dust/fume/gas/mist/vapours/spray.

Use only outdoors or in a well-ventilated area.

Response P301+P310 - If swallowed: Immediately call a poison center, doctor or medical center.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P312 - Call a poison center, doctor or medical center if you feel unwell.

Do NOT induce vomiting.

Storage Store locked up.

Protect from sunlight. Store in a well-ventilated place.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulation for hazardous

wastes.

3. COMPOSITION/INFORMATION ON INGREDIENTS

 COMPONENT
 CAS #
 Percent

 Chlorinated hydrocarbon
 156-60-5
 10 - 30

 Halogenated hydrocarbon
 406-58-6
 10 - 30

 Halogenated hydrocarbon
 811-97-2
 1-20

HMIS® III* HAZARDOUS WARNINGS:

Health: 1 Flammability: 1 Physical: 1 Personal See Section 8

Protective Equipment:

^{*} See www.paint.org/hmis or call the ACA at 1 (202) 462-6272 for more information on this current rating system.

4. FIRST AID MEASURES

Eyes: Immediately flush eyes gently with plenty of water for at least 15 minutes while holding eyelids apart. If symptoms persist or there

is visual difficulty, seek medical attention.

Skin Contact: In case of contact, immediately wash contaminated area with plenty of water for at least 15 minutes. Seek medical attention if

symptoms persist. Wash clothing before reuse.

Ingestion: Do not induce vomiting. Aspiration into the lungs can cause serious damage. Contact a physician, medical facility, or poison

control center immediately.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek immediate medical

attentior

NOTES TO PHYSICIAN:

This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used only in situations of emergency life support.

5. FIRE FIGHTING MEASURES

Fire and/or Explosion Hazards: This product contains a component(s) that is considered a flammable liquid, which has vapors that are heavier

than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point. Hazardous decomposition products may be formed (see Sec.10). "Empty" containers retain product residue and can be dangerous. Containers

may rupture or explode under fire conditions.

Fire Fighting Instructions: Use CO2, foam or dry chemical. Fire fighters should wear normal protective equipment and positive-pressure self-

contained breathing apparatus. Do not direct a solid stream of water or foam into hot burning pools, this may cause frothing and increase fire intensity. Apply water from a safe distance to cool container and protect surrounding area. Water is generally not effective and may spread fire; however, water spray may be used from a

safe distance to cool closed containers and protect surrounding area.

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Remove all sources of ignition. Wear appropriate personal protective equipment (PPE). Stop or reduce discharge if it can be done safely. Avoid run-off into storm sewers and ditches which may lead to natural waterways. Clean up with absorbent material. Place absorbent materials into container and close it tightly. Dispose of container properly. Ventilate contaminated area.

7. HANDLING AND STORAGE

Handling: Do not use near ignition sources. Avoid prolonged or repeated contact with skin. Avoid prolonged or repeated breathing of vapor. Use

with adequate ventilation. Avoid contact with eyes. Wash hands thoroughly after handling. Do not breathe vapor. May cause frostbite.

Storage: Store in a cool, dry, well ventilated area away from all sources of ignition. Empty container may contain residues which are hazardous.

Store away from oxygen cylinders or other oxidizing materials and possible ignition sources. Freezing will affect physical condition but

will not damage product. Thaw and mix before using. Do not store at temperatures above 122 degrees F.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Ventilation should be adequate to prevent exposures above the limits indicated below in this section of the SDS (from

known, suspected or apparent adverse effects). Local exhaust should be used in areas where exposure limits may be

exceeded. Mechanical ventilation should be used in confined spaces and low areas.

Eye Protection: Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as

chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid or

airborne material. Have an eye wash station available.

Skin Protection: The use of chemically resistant gloves is recommended if there is any possibility of prolonged or repeated liquid contact with

skin

Respiratory Protection: If respiratory irritation develops below the recommended exposure limits, use an NIOSH approved nuisance

dust/mist/organic vapor respirator. A supplied air respirator should be used if ventilation is not sufficient to maintain

exposure limits. Use NIOSH approved respirator where there is likelihood of inhalation of the product mist, spray or aerosol.

COMPONENT Chlorinated hydrocarbon	<u>CAS #</u> 156-60-5	ACGIH TLV 200ppm TWA	OSHA PEL Not established	OTHER Not established
Halogenated hydrocarbon	406-58-6	Not established	Not established	Not established
Halogenated hydrocarbon	811-97-2	Not established	Not established	1000ppm (mfr. recommend)

9. PHYSICAL AND CHEMICAL PROPERTIES

Not applicable Physical State: Aerosol can Lower Flammability Limit (%): Appearance: Clear Colorless Upper Flammability Limit (%): Not applicable Odor: Slight ethereal. Vapor Pressure (PSIG @ 70°F): No data available

Very faint Vapor Density [air = 1]: >1 Odor Threshold: pH: Not applicable Relative Density (H2O=1): 1 19

Solubility in Water: Melting/Freezing Point (°F): No data available Not determined Boiling Point (°F): No data available Partial Coefficient: n-No data available

octanol/water:

Flash Point (°F PMCC): Not applicable Autoignition Temperature (°F): Not applicable Evaporation Rate: Not determined Decomposition Temperature (°F): No data available Flammability (solid, gas): No data available Viscosity, dynamic (cSt): No data available

Percent VOCs (%): 60 - 80

10. STABILITY AND REACTION

Chemical Stability: Stable.

Conditions to Avoid: Avoid contact with: Ignition sources such as open flames, sparks, static discharges or glowing metal surfaces. Oxidizers.

Caustics. Powdered metals. Alkaline earth metals. Alkali. Strong bases. Magnesium. Zinc. Chemically active metals:

calcium, powdered aluminum, zinc, sodium, potassium, magnesium, etc.

Decomposition Products: Burning can produce the following combustion products: Hydrogen chloride. Carbon dioxide and carbon monoxide.

> Hydrogen fluoride. Phosgene. Fluorinated hydrocarbons. This material can be decomposed by extremely high temperatures (open flames, glowing metal surfaces, etc.) forming hydrofluoric acid and carbonyl fluoride.

11. TOXICOLOGICAL INFORMATION

No data available. Reproductive &

Developmental Toxicity:

IARC Carcinogen Designation: No data available

Ingredient CAS#

Toxicological Data Chlorinated hydrocarbon Dermal LD50 Rabbit 5 GM/KG 156-60-5

Oral LD50 Rat 1235 mg/kg Oral LD50 Mouse 2122 mg/kg

Inhalation LC50 Rat 24100 ppm 811-97-2 Inhalation LC50 Rat 1500 GM/M3

Halogenated hydrocarbon Inhalation LC50 Mouse 1700 GM/M3

12. ECOLOGICAL INFORMATION

Ecological Toxicity: No data available Mobility: No data available Degradability: No data available.

Ingredient CAS# **Toxicological Data**

Aquatic LC50 (96h) GUPPIES > 200 mg/L Halogenated hydrocarbon 406-58-6

48HR EC50 Daphnia > 200 mg/L 72HR EC50 Algae > 114 mg/L

13. DISPOSAL CONSIDERATIONS

Disposal: Dispose according to Federal, State and local regulations.

14. TRANSPORTATION INFORMATION

Proper Shipping name Agency **UN Number Hazard Class Packing Group** UN1950 Aerosols, Non-Flammable† Not applicable DOT 2.2 ID8000 9 Not applicable IATA Consumer Commodity† UN1950 Aerosols, Non- Flammable† 2.2 Not applicable IMDG

† "Limited Quantities" may be applicable for this transportation mode.

15. REGULATORY INFORMATION

Warning: This product contains the following chemicals that are subject to reporting requirements for the following regulatory bodies listed below:

COMPONENT % BY WEIGHT CAS# Regulatory Body Chlorinated hydrocarbon 156-60-5 10 - 30SARA Section 313

Toxic Substances Control Act

All components of this product are listed on the TSCA inventory.

California Prop 65

This product contains no California Proposition 65 ingredients that cause cancer, birth defects or other reproductive harm.

16. OTHER INFORMATION

Other Information : SDS Prepared by L. Dean Swartz, SDS Coordinator

Version Date: 12/11/2024

This information contained in this SDS is believed to be accurate as of the version date, but is not warranted to be. Since the use of this information and the conditions of use of this product are not within the control of Stoner Inc, it is the user's obligation to determine the conditions of safe use.

Stoner Incorporated 94052 PAGE 4